



NIS-K880C


AMD® Kabini/Stepped Eagle G-SOC high performance, full HD digital signage solution




AMD® Kabini/Stepped Eagle G-SOC



SODIMM DDR3 1066



VGA+HDMI



Gigabit LAN

Features

- AMD® Kabini/Stepped Eagle G-SOC
- Support Max.8GB DDR3 SODIMM
- AMD® Radeon™ HD8 series graphic media accelerator
- VGA+HDMI, Synch. Or Asynch. Display
- 4*USB2.0, 2*USB3.0, 1*RS232
- 1*full-size Mini-PCIe socket, support PCIe & USB device
- 1*half-size m-SATA socket
- 1*RTL8111E GbE LAN
- DC12V input
- FCC, CE, RoHScompliant

Specification

Processor	CPU	AMD® Kabini/Stepped Eagle G-SOC Quad Core CPU
	Chipset	AMD® Kabini/Stepped Eagle G-SOC
Memory	Architecture	Dual channel DDR3 800 / 1066 / 1333MHz FSB
	Capacity	Support max. 8GB
	Socket	1*200Pin DDR3 SO-DIMM
Display	Graphic Controller	AMD® Radeon™ HD8 series,Support Hardware Decode for 1080P MPEG-2, H.264 and VC-1 Playback, Support DirectX 11®, Support OpenGL 3.0
	VGA	1*standard DB15 VGA connector Max. Resolution: 1920 * 1080
	HDMI	Support HDMI 1.3, type A, 19pin Max. Resolution: 4K
	Dual Display	VGA + HDMI, Synch. Or Asynch. Display
	LAN	Controller
	WLAN	Support
Audio	Controller	Realtek HD ALC662 audio decoder(right&left channel)
Super I/O	USB	4*USB2.0/1.1 compatible, 2*USB3.0
	Serial Port	3-wire RS232
Expansion	Mini-PCIe	1*Mini-PCIe socket, support WIFI/3G wireless network
	USIM	1* inside SIM socket
Storage	SATA	1*SATA, max. transmission rate: 3Gb/s
	SSD	1*half-size M-SATA SSD
OS		Windows XP / XPE, Win7, Wes7, Win8, linux
Power	Adaptor	12V @ 5A
	Power Type	AC 110/220V
Environment	Operating Environment	0 ~ 45 °C
	Storage Environment	-20 ~ 70 °C
	Operating Humidity	0% ~ 90% relative humidity, non-condensing
	Storage Humidity	0% ~ 90% relative humidity, non-condensing
Form Factor	Dimensions	145mm *135mm *47mm (L*W*H)
	Weight	
	Installation	VESA
Regulatory Compliance		FCC, CE, RoHS compliant

Ordering Information

NIS-K880C-QF

AMD Stepped Eagle GX424CC 2.4GHz Quad Core CPU, SODIMM, HDMI/VGA , 1 x Giga LAN,4 x USB,1 x RS232,DC12Vinput

NIS-K880C-QS

AMD Kabini A6-5200 2.0GHz Quad Core CPU, SODIMM, HDMI/VGA , 1 x Giga LAN,4 x USB,1 x RS232,DC12Vinput

