



(All photos here are for reference only, Specifications are subject to the physical product.)




Intel@Brodwell™



SODIMM
DDR3L 1600



VGA+DVI



Gigabit LAN



Fanless

Specifications

Processor	CPU	SkyLake/KabyLake(R) U-series
	CPU Package	BGA On Board
	Chipset	SOC
	BIOS	System BIOS: SPI BIOS
Memory	Architecture	Dual Channel: DDR3L
	Capacity	Max. 32GB
	Socket	DDR3L SODIMM
Display	Graphic Controller	Integrated graphic card
	HDMI	HDMI port, max. resolution:4K@60Hz
Ethernet	Controller	LAN 1: Intel I211 GbE LAN (Optional POE)
		LAN 2: Intel I211 GbE LAN (Optional POE)
		LAN 3: Intel I211 GbE LAN (Support BYPASS)
		LAN 4: Intel I211 GbE LAN (Support BYPASS)
		LAN 5: Intel I211 GbE LAN (Optional POE)
		LAN 6: Intel I211 GbE LAN (Optional POE)
		Network LED SPEED/LINK 6 set of bilayer
Super I/O	Controller	NT6102, support system temp. monitoring.
	Watch Dog Timer	0~255sec., providing Watch Dog program.
TPM	Controller	N/A
I/O	USB 3.0	4*USB 3.0/2.0 PORT
	USB 2.0	2*USB 2.0 PORT
	Serial Port	Com1 9-wire RS232 RJ45 port
	Parallel Port	N/A
	PS/2	N/A
	GPIO	N/A
	IEEE1394	N/A
	PCIe x1	N/A
	Mini-PCIe	1* full-size Mini-PCIe socket, support PCIe & USB device
	UIM Socket	3G UIM Card socket
Storage	SATA	1* standard 7Pin SATA-III & power connector, transmission rate: max.3Gb/s
	M-SATA	1* full-size Mini-PCIe socket, support M-SATA SSD, transmission rate: max.3Gb/s
Power	Power Type	AT/ATX(optional), DC 12V input, support power reverse & over-voltage protection.
	Power Consumption	Support max. 50W (including POE)
FRONT_PANEL		POWER LED
		HDD LED
		RESET
		POWER BUTTOM
Environment	Operating Temp.	-10°C ~ 60°C
	Storage Temp.	-40°C ~ 80°C
	Operating Humidity	0% ~ 90% relative humidity, non-condensing
	Storage Humidity	0% ~ 90% relative humidity, non-condensing
Formfactor	Dimensions	215 x 136 x 60mm
	Weight	
Certificate		FCC, CE, RoHS

Features

Ordering Information

