



(All photos here are for reference only, Specifications are subject to the physical product.)

Specifications

Processor	CPU	Onboard Intel® Celeron® SkyLake U-series CPU, fanless	
Memory	Architecture	DDR3L SODIMM+ON Board (Option)	
Network	3G/4G	Support 3G/4G communication module, Mini-PCIe interface, pop-up SIM card	
	Controller	LAN1:	Intel I210 GbE LAN, RJ45, POE
		LAN2:	Intel I210 GbE LAN, RJ45, POE
		LAN3:	Intel I210 GbE LAN, RJ45, POE
		LAN4:	Intel I210 GbE LAN, RJ45, POE
LAN5:		Intel I210 GbE LAN, RJ45	
H/W Monitor	Watch Dog Timer	0~255 sec., providing Watch Dog Program	
Storage	Expansion Storage	SODIMM socket, MAX 8GB	
Front Panel	Power	9~36V DC external power input jack	
	Indicator	Hard disk and power supply indicator	
	Switch	Power switch with LED	
	HDMI	2*HDMI port, max.resolution:4K@60Hz	
	I/O interface	Com1 9-wire RS232 TX/RX signal, support 4000V surge protection, +5V/+12V/RING	
	LAN	2* USB 3.0/2.0 PORT	
		LAN1:	Intel I210 GbE LAN, RJ45, Speed/Link LED, POE
LAN2:		Intel I210 GbE LAN, RJ45, Speed/Link LED, POE	
LAN3:		Intel I210 GbE LAN, RJ45, Speed/Link LED, POE	
LAN4:		Intel I210 GbE LAN, RJ45, Speed/Link LED, POE	
Rear Panel	I/O interface	4* USB 3.0/2.0 PORT	
	Indicator	Network signal indicator	
Power	Power Consumption	Support max.50W(Including POE)	
Environment	Operating Temp.	-20°C ~ 70°C	
	Storage Temp.	-40°C ~ 80°C	
	Operating Humidity	0% ~ 90% relative humidity, non-condensing	
	Storage Humidity	0% ~ 90% relative humidity, non-condensing	
Formfactor	Dimensions	215 × 136 × 60mm	
	Weight	1.4KG (Net weight)	
Certificate		3C, FCC, CE, RoHS	




Intel@SkyLake



SODIMM
DDR3L 1600



HDMI



Gigabit LAN



Fanless

Features

- Intel® 6th/7th gen. SkyLake series low power processor
- SODIMM DDR3L low voltage memory socket
- Intel® HD Graphics integrated graphics
- 2* HDMI port, max.resolution:4K@60Hz
- 5* I210 GbE Lan, 6* USB3.0/2.0 Port
- 1* RS232 TX/RX signal
- 1* Mini PCIe×1, 1* SATA, 1* M-SATA
- Support 3G/4G communication module
- DC9~36V input

Ordering Information

NIS-S990B-CL

Intel® Celeron® 3885U 1.6GHz CPU, 2*HDMI display, 5*I210 GbE LAN, 1*RS232, 6*USB3/2.0 Port, 1*MiniPCIe×1, 1*SATA, 1*M-SATA, Support 3G/4G communication module, DC 9~36V input, support power reverse and overvoltage protection

NIS-S990B-i3

Intel® Core® i3-6100U 2.3GHz CPU, 2*HDMI display, 5*I210 GbE LAN, 1*RS232, 6*USB3/2.0 Port, 1*MiniPCIe×1, 1*SATA, 1*M-SATA, Support 3G/4G communication module, DC 9~36V input, support power reverse and overvoltage protection

NIS-S990B-i5

Intel® Core® i5-6200U 2.3GHz CPU, 2*HDMI display, 5*I210 GbE LAN, 1*RS232, 6*USB3/2.0 Port, 1*MiniPCIe×1, 1*SATA, 1*M-SATA, Support 3G/4G communication module, DC 9~36V input, support power reverse and overvoltage protection

NIS-S990B-i7

Intel® Core® i7-6500U 2.3GHz CPU, 2*HDMI display, 5*I210 GbE LAN, 1*RS232, 6*USB3/2.0 Port, 1*MiniPCIe×1, 1*SATA, 1*M-SATA, Support 3G/4G communication module, DC 9~36V input, support power reverse and overvoltage protection

